

SEND THE INQUIRY

+358 103 195 100

Standards:

DIN 965
ISO 7046
PN 82208

4.8

Luokka:

B

POWŁOKA
CYNKOWA
BIAŁA

Pinnoite tyyppi:

A
POWŁOKA
CYNKOWA
ZŁOTAC
POWŁOKA
CYNKOWA
CZARNĄN
POWŁOKA
NIKLOWA

Pinnoite - pyynnöstä :



Dimensions

Material index	d	L [mm]	D [mm]	b [mm]	Avainkolo	Mekaaninen luokitus	Pinnoite tyyppi	Yksikkö
1307060090PZBT	M6	90	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307060085PZBT	M6	85	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307080080PZBK	M8	80	14.5	28	PZ 4	4.8	B - ocynk biały	KG
1307060080PZBT	M6	80	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307050080PZBT	M5	80	9.2	22	PZ 2	4.8	B - ocynk biały	TYS
1307050070PZBT	M5	70	9.2	22	PZ 2	4.8	B - ocynk biały	TYS
1307060070PZBT	M6	70	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307080070PZBT	M8	70	14.5	28	PZ 4	4.8	B - ocynk biały	TYS
1307080070PZBK	M8	70	14.5	28	PZ 4	4.8	B - ocynk biały	KG
1307080060PZBK	M8	60	14.5	28	PZ 4	4.8	B - ocynk biały	KG
1307060060PZBT	M6	60	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307080060PZBT	M8	60	14.5	28	PZ 4	4.8	B - ocynk biały	TYS
1307050060PZBT	M5	60	9.2	22	PZ 2	4.8	B - ocynk biały	TYS
1307050050PZBT	M5	50	9.2	22	PZ 2	4.8	B - ocynk biały	TYS
1307060120PZBT	M6	120	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307060100PZBT	M6	100	11.0	25	PZ 3	4.8	B - ocynk biały	TYS
1307050100PZBT	M5	100	9.2	22	PZ 2	4.8	B - ocynk biały	TYS