



Luokka:

Pinnoite tyyppi:

SEND THE INQUIRY

+358 103 195 100

Standards:

DIN 913  
ISO 4026  
PN-M 82314

45H

B  
POWŁOKA  
CYNKOWA  
BIAŁA

OX  
OKSYDOWANE



Dimensions

| Material index    | d  | L [mm] | s [mm] | Mekaaninen luokitus | Pinnoite tyyppi         |
|-------------------|----|--------|--------|---------------------|-------------------------|
| 1201040004IMB913T | M4 | 4      | 2      | 45H                 | B - ocynk biały         |
| 1201040004IMO913T | M4 | 4      | 2      | 45H                 | OX - powłoka oksydowana |
| 1201040005IMO913T | M4 | 5      | 2      | 45H                 | OX - powłoka oksydowana |
| 1201040006IMB913T | M4 | 6      | 2      | 45H                 | B - ocynk biały         |
| 1201040006IMO913T | M4 | 6      | 2      | 45H                 | OX - powłoka oksydowana |
| 1201040008IMB913T | M4 | 8      | 2      | 45H                 | B - ocynk biały         |
| 1201040008IMO913T | M4 | 8      | 2      | 45H                 | OX - powłoka oksydowana |
| 1201040010IMO913T | M4 | 10     | 2      | 45H                 | OX - powłoka oksydowana |
| 1201040012IMB913T | M4 | 12     | 2      | 45H                 | B - ocynk biały         |
| 1201040016IMB913T | M4 | 16     | 2      | 45H                 | B - ocynk biały         |
| 1201040020IMB913T | M4 | 20     | 2      | 45H                 | B - ocynk biały         |
| 1201040020IMO913T | M4 | 20     | 2      | 45H                 | OX - powłoka oksydowana |
| 1201050004IMB913T | M5 | 4      | 2.5    | 45H                 | B - ocynk biały         |
| 1201050004IMO913T | M5 | 4      | 2.5    | 45H                 | OX - powłoka oksydowana |
| 1201050005IMB913T | M5 | 5      | 2.5    | 45H                 | B - ocynk biały         |
| 1201050008IMO913T | M5 | 8      | 2.5    | 45H                 | OX - powłoka oksydowana |
| 1201050010IMB913T | M5 | 10     | 2.5    | 45H                 | B - ocynk biały         |
| 1201050010IMO913T | M5 | 10     | 2.5    | 45H                 | OX - powłoka oksydowana |

| Material index    | d   | L [mm] | s [mm] | Mekaaninen luokitus | Pinnoite tyyppi         |
|-------------------|-----|--------|--------|---------------------|-------------------------|
| 1201060006IMB913T | M6  | 6      | 3      | 45H                 | B - ocynk biały         |
| 1201060006IMO913T | M6  | 6      | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060008IMB913T | M6  | 8      | 3      | 45H                 | B - ocynk biały         |
| 1201060008IMO913T | M6  | 8      | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060010IMO913T | M6  | 10     | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060012IMB913T | M6  | 12     | 3      | 45H                 | B - ocynk biały         |
| 1201060012IMO913T | M6  | 12     | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060014IMO913T | M6  | 14     | 3      | 45H                 | B - ocynk biały         |
| 1201060016IMB913T | M6  | 16     | 3      | 45H                 | B - ocynk biały         |
| 1201060016IMO913T | M6  | 16     | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060020IMB913T | M6  | 20     | 3      | 45H                 | B - ocynk biały         |
| 1201060020IMO913T | M6  | 20     | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060025IMO913T | M6  | 25     | 3      | 45H                 | OX - powłoka oksydowana |
| 1201060030IMB913T | M6  | 30     | 3      | 45H                 | B - ocynk biały         |
| 1201080008IMB913T | M8  | 8      | 4      | 45H                 | B - ocynk biały         |
| 1201080008IMO913T | M8  | 8      | 4      | 45H                 | OX - powłoka oksydowana |
| 1201080010IMO913T | M8  | 10     | 4      | 45H                 | OX - powłoka oksydowana |
| 1201080012IMB913T | M8  | 12     | 4      | 45H                 | B - ocynk biały         |
| 1201080012IMO913T | M8  | 12     | 4      | 45H                 | OX - powłoka oksydowana |
| 1201080020IMB913T | M8  | 20     | 4      | 45H                 | B - ocynk biały         |
| 1201080020IMO913T | M8  | 20     | 4      | 45H                 | OX - powłoka oksydowana |
| 1201080025IMB913T | M8  | 25     | 4      | 45H                 | B - ocynk biały         |
| 1201100010IMB913T | M10 | 10     | 5      | 45H                 | B - ocynk biały         |
| 1201100010IMO913T | M10 | 10     | 5      | 45H                 | OX - powłoka oksydowana |
| 1201100012IMO913T | M10 | 12     | 5      | 45H                 | OX - powłoka oksydowana |
| 1201100020IMO913T | M10 | 20     | 5      | 45H                 | B - ocynk biały         |
| 1201100025IMB913T | M10 | 25     | 5      | 45H                 | B - ocynk biały         |